

STATE OF MICHIGAN

Request For Proposal No. 250000001056

Small Class of Non-Lift and Lift Transit Buses

CLASS 1: Minimum 5 Years/150,000 Miles

CLASS 2: Minimum 7 Years/200,000 Miles

SCHEDULE G EQUIPMENT CHECKLIST

I	Instructions: Complete each section of the following Equipment Checklist document. If applicable, provide as much detail as possible, in the evaluation portion, by listing product and model names, sizes, materials used, type, etc. <u>Failure to complete this document and return with your bid package shall result in a bid disqualification.</u>			
II	BODY SPECIFICATIONS			
		Item	Product Name and Model	Size, Material, and/or Type
A.		General design and construction	Class 1: Vanterra Class 2: Terra Transit	Steel cage construction that meets all applicable FMVSS and Buy America regulations including the FMVSS 220 rollover test. Both class buses meet the Altoona test requirements. The Class 1 bus is built on the Ford E350 chassis and the Class 2 bus is built on the Ford E450 chassis.
B.	1.	Body structure and exterior panels	Turtle Top	The sidewall construction consists of vertical 1" x 2" x 16-gauge steel wall tubes welded to a horizontal 14-gauge 1" x 3" steel tube at the top and a 1" x 1" x 16-gauge steel tube at the bottom. Both the header and footer tubes run the full length of the unit body on both sides. All steel is primered per specifications. Crance Composites Nobel Select Exterior Sidewall Panels are used for the external body sidewalls. The composite material is a high gloss, exterior, gel-coated panel with UV protection and environmental properties. The external body consists of one individual panel from the roof line to the skirt, which reduces seams in the exterior.
	2.	Rollover frame, steel cage type	Turtle Top	Steel frame construction consists of 11-gauge U-shaped mounting rails that span the OEM chassis frame. 13-gauge formed channels are spaced across the mounting rails and extend the full width of the body at approx. 22" intervals to form cross members. The frame is finished with a 2" x 2" x 11-gauge steel angle around the perimeter. Each vehicle has OEM standard cross-members. 7-gauge steel frame extensions are welded at the rear of the OEM frame rails on extended models.
	3.	Body section thickness	Turtle Top	Wall thickness is 1.2"
	4.	Body section thickness	Turtle Top	Wall thickness is 1.2"

Transportation Equipment Sales Corporation – Turtle Top

	5.	Exterior panels	Crane Composites	Nobel Select Exterior high gloss FRP.
	6.	Interior panels	Turtle Top	FRP as specified
	7.	Interior length	Turtle Top	Varies per floorplan, please refer to floorplans
	8.	Interior width	Turtle Top	Class I: 79.75" Class II: 93.78"
	9.	Interior height	Turtle Top	Class I: 75" Class II: 80" or 77" when using raised floor
	10.	Exterior length	Turtle Top	Varies per floorplan, please refer to floorplans
	11.	Exterior width	Turtle Top	Class I: 84" Class II: 96.25"
	12.	Exterior height	Turtle Top	Class I: 109" Class II: 117" Height does not include optional items such as rooftop air conditioning system.
	13.	Rubrails	Turtle Top	Aluminum custom extrusion w/ a rubber bumper
	14.	Body overhang	Turtle Top	Varies per floorplan, please refer to floorplans
C.	1.	Passenger door	A&M Electric	Aluminum door, electrically operated
	2.	Opening Size	A&M Electric	36" or 42" clear opening
D.		Stepwell	Turtle Top	304 Stainless steel
E.		Interior – Color	Turtle Top	Light gray
F.		Flooring	Gerflor Sirius	Subfloor – Coosa BW20 3/4" Composite Panel flooring with Altro Storm Gray floor covering
G.		Emergency exits	Turtle Top, Transpec #1970	Pushout egress windows, rear door or window as specified, Transpec roof hatch
H.		Gauges	Ford	Standard OEM Gauges per specification
I.		Fare box	Diamond NV	Diamond NV Rectangular Farebox w/2 Vaults
J.		Bumpers	OEM Front/ Romeo Rim Rear	OEM front and Romeo Rim energy absorbing rear bumper as specified
K.		Mud Flaps and Splash Guards	Turtle Top	Rubber composite front and rear with T brackets as specified. No self-tapping screws used.
L.		Towing	Fastenal	Rear tow hooks per spec
M.	1.	Undercoating	Z-Tech	Spray type undercoat body and cab per specification
	2.	Rustproofing	Turtle Top	All box type steel tubing (except stainless steel) used in the floor structure and sidewall structure from the top of the window down, has the interior of the tube coated with corrosion resistant material conforming to MIL-C-62218
N.	1.	Interior mirrors	Rosco	Convex interior mounted as specified at pilot
	2.	Sunvisors	Ford OEM	OEM
O.		Exterior Mirrors	Rosco Accustyle	Power remote and heated
P.	1.	Seats – Driver	Ford OEM	OEM Ford driver seat with arm rest
	2.	Seats – Passenger	Freedman Featherweight	Freedman mid-high seats per floor plan requirements. All with required USR seatbelts, grab handles and seat covers where applicable. Level 5 fabric on vinyl seats and Level 7 fabric on cloth seats.
	3.	Seats – Fold-up	Freedman Featherweight Fold-a-way	Featherweight folding per specification. Level 5 fabric on vinyl seats and Level 7 fabric on cloth seats.

Transportation Equipment Sales Corporation – Turtle Top

	4.	Seats – Flip-up	Freedman Featherweight Flip-up	Featherweight flip per specification, Level 5 fabric on vinyl seats and Level 7 fabric on cloth seats.
Q.		Handrails, stanchions	Turtle Top	Powdercoat yellow where specified and stainless steel where specified
R.		Interior lighting – LED	Various approved OEM	All LED as specified
S.		Exterior lighting - LED	Ford OEM/Maxxima	All LED as specified
T.	1.	Heating / ventilating – Front System	Ford	As specified
	2.	Heating / ventilating – Rear System	Valeo	Heater size and location may vary with floorplan
U.		Windows	Lippert	Tinted T-slide with egress windows on sides and rear when applicable
V.		Paint	Azko Nobel	Paint Per Specifications
W.		Insulation	Turtle Top	Closed cell foam 1” type #1 density EPS expanded polystyrene to meet specification
X.		Lift (platform type)	Braun	1,000lb capacity 37” wide x 54” long platform
III	WHEELCHAIR SECUREMENT AREA			
		Item	Product Name and Model	Size, Material, and/or Type
A.		Wheelchair securement	Class 1: Ford E350 Class: Ford E450	Per floorplan
B.		Wheelchair restraints	Q-Straint QRT-360	With retractable shoulder harness
C.		Restraint storage system	Freedman TDSS	TDSS under foldaway seats plus one storage bag as requested
IV	CHASSIS SPECIFICATIONS			
		Item	Product Name/Model	Size, Material, and/or Type
A.		Chassis	Class 1: Ford E350 Class: Ford E450	Class I: 12,500# GVWR Class II: 14,500# GVWR
B.		Tilt Wheel/Power Steering	Ford	OEM
C.	1.	Wheelbase – 138” minimum (Class 1)	Ford	138”
	2.	Wheelbase – 158” minimum (Class 2)	Ford	158” – 176” depending on floorplan
D.		Class 1- Gasoline	Ford	7.3L V8 Gasoline Premium
		Class 1- CNG	Not Available	Not Available
		Class 1 - Propane	A-1 Alt Fuels OPTION ONLY	EPA Certified Dedicated 24 GGE LPG Bi-Fuel System, Minimum 85" rear overhang, Tanks mounted underbody.
		Class 2 -Gasoline	Ford	7.3L V8 Gasoline Premium
		Class 2 – CNG	A-1 Alt Fuels OPTION ONLY	EPA Certified Dedicated 38 GGE CNG System minimum 158" W/B, minimum 85" rear overhang, 66" of available space required on outside frame rail - street-side, Four tanks (type 1 & 3) mounted underbody with Auxiliary Regulator
		Class 2 - Propane	Dedicated: Roush Bi-Fuel: A-1 Alt Fuels	Dedicated System: EPA Certified Dedicated 40 or 64 GGE LPG System, Minimum 85" rear overhang, Tanks mounted underbody.

Transportation Equipment Sales Corporation – Turtle Top

			OPTION ONLY	Bi-Fuel System: EPA Certified Dedicated 24 GGE LPG System, requires 56" of space on driver side outer frame rail, Tanks mounted underbody.
E.		Auxiliary Coolant Heater	Espar – OPTION ONLY	Espar htr to heat coolant per specs and addendum - OPTION ONLY
F.		Transmission	Ford	Electronic control six speed automatic with overdrive
G.		Alignment	Ford	Four wheel per specification
H.		Gross Vehicle Weight Rating (GVWR)	Ford	Class I: 12,500 lbs Class II: 14,500 lbs
		Front axle rating	Ford	Class I: 5,000 lbs Class II: 5,000 lbs
		Rear axle rating	Ford	Class I: 8,500 lbs Class II: 9,600 lbs
I.		Differential	Ford	Class I: 4.10 Gear Ratio Class II: 4.56 Gear Ratio
J.		Battery	Ford	750 CCA
K.		Battery Cables and Grounds	Ford	Protective cover on terminals with no exposed copper as specified
L.		Alternator	Ford	240 Amp
M.		Engine Fast Idle	Intermotive	AFIS
N.		Brakes	Ford	OEM 4 wheel disc w/ABS
O.		Fuel tank	Ford	Class I: 40 gallon Class II: 55 gallon
P.		Hazard flashers	Ford	OEM
Q.		Shock absorbers	Ford	OEM
R.		Suspension - Front	Ford	OEM
S.		Suspension - Rear	Ford	Rigid axle, leaf with extra spring for wheelchair lift
T.		Stabilizer	Ford	OEM
U.		Wheels	Ford	16" steel OEM painted with dual rear wheel
V.		Tires	Ford	LT225/75R16E Ford OEM
W.		Drive shaft	Ford	With shaft guards as specified
X.		Wipers / Horn	Ford	OEM
Y.		Radiator and cooling system	Ford	OEM
Z.		Fluids	Ford	OEM
AA.		Engine Cover/Trim	Ford	Engine is under hood/doghouse and insulated by OEM
AB.		Exhaust system	Ford	Exhaust per specification except where regulation prevents modification

Transportation Equipment Sales Corporation – Turtle Top

EQUIPMENT CHECKLIST

V OTHER ITEMS				
		Item	Product Name and Model	Size, Material, and/or Type
A.	1.	Safety – Fire extinguisher	Amerex ABC	5lb mounted vertically per specification
	2.	Safety – Reflective triangles	Turtle Top	3 Orange Reflective Triangles
	3.	Safety – Reverse alarm	Turtle Top	97 dba mounted per specification
	4.	Safety-Rear door alarm	Intermotive	Gateway
	5.	Safety- Exterior height (clearance) decal	Turtle Top	Per Specification
	6.	Safety-Lift interlock system	Intermotive	Lift Interlock
	7.	Safety-Warning/engine shutdown system	Ford	OEM
	8.	Safety-Headlight control	Ford	OEM
	9.	Safety-Strobe light	Innotec – OPTION ONLY	Mounted 6” from rear of bus
B.	1.	Lift circuit breaker	Braun	Installed per specification
	2.	12-volt power point	Ford	OEM
	3.	Wire coding and harnesses	Turtle Top	Per specification
	4.	Electrical panel	Turtle Top	Fused
	5.	Wiring support	Turtle Top	As specified
	6.	Wiring grounds and capacity	Turtle Top	As specified
	7.	Constant run solenoid	Turtle Top	As specified
	8.	Circuit capacity & function	Turtle Top	As specified
	9.	Wiring protection	Turtle Top	As specified
	10.	Wiring routing	Turtle Top	As specified
	11.	Wiring connections	Turtle Top	Weatherpak per specifications
VI OPTIONS – ALTERNATE QUOTES				
1		Air Conditioning – Split System – both rooftop & Skirt mounted condenser	Trans Air	Skirt Mount: ACN773S: TA77 EVAPORATOR, SMC3L THREE FAN SKIRT MOUNT CONDENSER AND 15 CID COMPRESSOR. EC4.0 Controls Roof Mount: ACN77R90S: INCLUDES TA77 EVAPORATOR, R90 ROOF MOUNT CONDENSER AND 15 CID COMPRESSOR. REQUIRES #16 HOSE , EC4.0

Transportation Equipment Sales Corporation – Turtle Top

				Controls, branchguard
2		Air Conditioning - Rooftop System	Trans Air	ACNRT80: ALL-IN-ONE RT80 SYSTEM w/HEAT AND 15 CID COMPRESSOR. #16 HOSE, EC4.0 Controls, coolant booster pump, branchguard.
3		Auxiliary Coolant Heater	Espar	Hydronic S3 B5E CS with EasyStart Pro controller
4		Auxiliary Air Heater	Espar	Airtronic B4L with EasyStart Pro controller
5		Destination Sign – Roller Curtain	Transign	Per specifications
6		Destination Sign – LED	Transign	12x112 Display with OCU Led
7		Donation box (in lieu of standard farebox – deduct)	Diamond	D donation box
8		Driver Side Running Board/Steps/Grab Handle	Turtle Top	Wide Diamond Plate
9		Farebox Electrical Prep Only (less standard farebox- deduct)	Turtle Top	power & ground per specifications
10		Limited Slip Differential	Ford	OEM
11		Rear Emergency Exit Window	CleerVision	Rear egress window as specified
12		Paint - One stripe	AkzoNobel	Per specification
13		Paint - Roof second color	AkzoNobel	Per specification
14		Paint - Different Full body	AkzoNobel	Per specification
15		Reflective Vinyl Belt Stripe	Turtle Top	Per specification
16		Lift – Type I (in lieu of standard lift - deduct)	Braun	NCL1000IB3754HB -2 Century Series, 37” wide, 1,000 lbs
17		Lift – Type II – Powered outer barrier (in lieu of standard lift)	Not available	Not available
18		Lift - Folding Platform (in lieu of standard lift)	Not available	Not available
19		Wheelchair Single Point Securement System (in lieu of one standard L-Track position)	Q-straint	360-QRT Slide-n- Click
20		Recessed Wheelchair Securement Station	Q-straint	Q-Straint ONE System
21		Additional Wheelchair Position – L Track System	Q-straint	360-QRT L-Track
22		Additional Wheelchair Position – Single Point System	Q-straint	360-QRT Slide-n- Click
23		Portable Oxygen Tank Holder	Surelok	GO2 single tank holder
24		Assistive Blue Loop Straps	Q-straint	Blue webbing loops
25		Two-way radio prep package	Turtle Top	Prep includes two radio ground planes on roof with access panels and wiring per specification
26		Radio - AM/FM stereo system w/ four speakers	Ford / Turtle Top	OEM radio and antenna with 4 speakers

Transportation Equipment Sales Corporation – Turtle Top

27		Public Address (PA) System Only w/ two speakers	REI	PA System, with Hand Held Mic & Clip and 2 Speakers
28		Radio – AM/FM/PA System w/ four speakers	REI	PA System, With Hand Held Mich & Clip and 4 speakers
29		Radio – Speaker only (additional)	ASA	5 ¼”
30		Raised Flooring (No Wheel Wells)	Turtle Top	Per specifications
31		Entrance Stepwell Heater	Warm Welcome	Per specifications
32		Manual Entrance Door	Turtle Top	Manual Door mechanism with rod and handle
33		Seating – Forward Facing Standard Double Seat – Vinyl	Freedman Featherweight	Mid-Back with USR belts, grab handles
34		Seating – Forward Facing Standard Double Seat – Fabric	Freedman Featherweight	Mid-Back with USR belts, grab handles
35		Seating – Forward Facing Standard Double Seat – Vinyl (Deduct)	Freedman Featherweight	Deduct standard vinyl seat
36		Seating – Forward Facing Standard Double Seat – Fabric (Deduct)	Freedman Featherweight	Deduct standard cloth seat
37		Seating – Forward Facing Double Fold-A-Way – Vinyl	Freedman Featherweight	3-Step folding double seat with USR belts, grab handles
38		Seating – Forward Facing Double Fold-A-Way – Fabric	Freedman Featherweight	3-Step folding double seat with USR belts, grab handles
39		Seating – Forward Facing Double Fold-A-Way – Vinyl (Deduct)	Freedman Featherweight	Deduct standard folding vinyl seat
40		Seating – Forward Facing Double Fold-A-Way – Fabric (Deduct)	Freedman Featherweight	Deduct standard folding cloth seat
41		Seating - Single Pivot Folding Seat	Freedman Featherweight	Single Pivot seat with 360 turn capabilities
42		Seating – Single Flip-up – Vinyl	Freedman Featherweight	Single flip seat with USR belts, grab handles, armrest (if applicable)
43		Seating – Single Flip-up – Fabric	Freedman Featherweight	Single flip seat with USR belts, grab handles, armrest
44		Seating – Double Flip-up – Vinyl	Freedman Featherweight	Double flip seat with USR belts, grab handles, armrest (if applicable)
45		Seating – Double Flip-up – Fabric	Freedman Featherweight	Double flip seat with USR belts, grab handles, armrest (if applicable)
46		Seating – Double w/Single Integrated Child Seat (ICS) - Vinyl	Freedman Featherweight	ICS seat with adult companion with USR belts, grab handles
47		Seating – Double w/Single Integrated Child Seat (ICS) – Fabric	Freedman Featherweight	ICS seat with adult companion with USR belts, grab handles

Transportation Equipment Sales Corporation – Turtle Top

48		Seating – Double w/Single Integrated Child Seat (ICS) – Vinyl (Deduct)	Freedman Featherweight	Deduct standard ICS vinyl seat
49		Seating – Double w/Single Integrated Child Seat (ICS) – Fabric (Deduct)	Freedman Featherweight	Deduct standard ICS cloth seat
50		Seating – Double w/Double Integrated Child Seat (ICS) - Vinyl	Freedman Featherweight	Double ICS seat with USB belts, grab handles
51		Seating – Double w/Double Integrated Child Seat (ICS) - Fabric	Freedman Featherweight	Double ICS seat with USB belts, grab handles
52		Power Seat Base (Driver)	Shield (Adnik)	Power base
53		Alternate Engine - CNG Class I	Not Available	Not Available
54		Alternate Engine - CNG Class II	A-1 Alt Fuels	EPA Certified Dedicated 40 GGE CNG System minimum 158" W/B, minimum 85" rear overhang, 66" of available space required on outside frame rail - street-side, Four tanks (type 1 & 3) mounted underbody with Auxiliary Regulator
55		Alternate Engine LPG 40 GGE Class I	Not Available	Not Available
56		Alternate Engine LPG 40 GGE Class II	Dedicated: Roush Bi-Fuel: A-1 Alt Fuels	Dedicated System: EPA Certified Dedicated 41 GGE LPG System, Minimum 85" rear overhang, Tanks mounted underbody. Bi-Fuel System: EPA Certified Dedicated 24 GGE LPG System, Minimum 85" rear overhang, Tanks mounted underbody.
57		Alternate Engine LPG 64 GGE Class I	Not Available	Not Available
58		Alternate Engine LPG 64 GGE Class II	Dedicated: Roush Bi-Fuel: A-1 Alt Fuels	Dedicated System: EPA Certified Dedicated 64 GGE LPG System, Minimum 85" rear overhang, Tanks mounted underbody.

Transportation Equipment Sales Corporation – Turtle Top

				Bi-Fuel System: EPA Certified Dedicated 24 GGE LPG System, requires 56" of space on driver side outer frame rail, Tanks mounted underbody.
59		Stop Request System	RC Tronics ADA Compliant	With pull cords, driver alert and push button at wheelchair locations
60		Back-up Sensor System	Rosco	BSSK-1000
61		Back-up Camera System	Rosco	Per specification
62		Video Surveillance – Two Camera System	Safety Vision	DVR, 2 CAMERAS, CABLES, ACCELEROMETE R, DRIVER SENSOR, GPS ANTENNA
63		Video Surveillance – Four Camera System	Safety Vision	DVR, 4 CAMERAS, CABLES, ACCELEROMETE R, DRIVER SENSOR, GPS ANTENNA
64		Video Surveillance – Six Camera System	Safety Vision	DVR, 6 CAMERAS, CABLES, ACCELEROMETE R, DRIVER SENSOR, GPS ANTENNA
65		Video Surveillance – DVR System Upgrade	Safety Vision	1 TB ILO 500GB
66		Video Surveillance – Extra Interior Cameras	Safety Vision	EXTRA CAMERA AND CABLE
67		Video Surveillance – Extra Exterior Cameras	Safety Vision	EXTRA CAMERA AND CABLE
68		Video Surveillance Prep Package	Turtle Top	Pre-wire
69		Rear Suspension Assist System - A	Mor/Ryde	RS
70		Rear Suspension Assist System - B	Liquid Spring	Hydraulic
71		Spare Tire - Steer Axle	Ford	OEM
72		Spare Tire - Drive Asle	Ford	OEM
73		Entry Door Grab Handles	Turtle Top	Per specifications
74		Interior Mirror	Rosco	Per specifications
75		Ceiling Handrails	Turtle Top	1-1/4" with curved ends
76		Wheelchair Lift Plexiglass Barriers	Turtle Top	Per specifications
77		Slide-out Battery Tray	Turtle Top	Stainless steel pull out tray per specifications
78		Bike Rack	Sportswork	Apex 2
79		Bike Rack – 3 Position	Sportswork	Apex 3
80		Yellow Seatback Grab Handles	Freedman	Anti-vandal yellow
81		OEM Chassis Cruise Control	Ford	OEM
82		Blind Spot Assist Mirrors	Safety Vision	Electronic mirror monitor with side exterior cameras – TESCO is not responsible if this option is chosen but

Transportation Equipment Sales Corporation – Turtle Top

				it doesn't meet state laws.
--	--	--	--	-----------------------------

EQUIPMENT CHECKLIST

VII		VENDOR / MANUFACTURER REQUIREMENTS	List electronic file names
A		Bus information furnished	Turtle Top-VII-A Bus Information.pdf
B		Manufacturer quality control (name/title)	Turtle Top-VII-B-Quality Control QVM Summary with forms.pdf Matt Sausaman General Manager matts@turtletop.com
C		Air conditioning certification	Turtle Top -VII-C Air Conditioning Letter.pdf
D		Heating/Ventilating certification	Turtle Top -VII-D Heating Letter.pdf
E		Purchaser inspection	Turtle Top -VII-E Purchaser Inspection.pdf Primary Inspection Point: Turtle Top Bus 67819 IN-15 New Paris, IN 46553
F		Warranty	Turtle Top-I-Warranty.pdf
VIII		DOCUMENTS & DRAWINGS	List electronic file names
A.		The Michigan request for proposal (RFP) and bus specification forms completed in detail.	Turtle Top-A-RFP Instructions - Confidential Treatment Form - Vendor Questions Worksheet.pdf Turtle Top-A-Schedule A - Statement of Work.dpdf Turtle Top-A-Schedule B - Pricing.xlsx Turtle Top-A-Schedule C - Insurance Requirements.docx Turtle Top-A-Schedule D - Small Bus Specifications.pdf Turtle Top-A-Schedule E - Federally Required Contract Clauses Signed By TESCO.pdf Turtle Top-A-Schedule E - Federally Required Contract Clauses Signed By TT.pdf Turtle Top-A-Schedule G - Equipment Checklist.pdf Turtle Top-A-Schedule H - MDOT Transit Agency Listing AD1.pdf

Transportation Equipment Sales Corporation – Turtle Top

			Turtle Top-A-Standard Terms.docx
B.		Bus floor plans indicating dimensions and showing the interior layout of the bus. The plan shall include wheelchair placement, stanchion locations, engineering calculated loaded bus axle weights, and be drawn to scale for all configurations.	Turtle Top-B-Floorplans and WA.pdf
C.		Detailed engineering drawing for the design of the entrance door and door-opening device.	Turtle Top-C-D-E-G Construction.pdf
D.		Detailed engineering drawing for the design of the entrance step configuration.	Turtle Top-C-D-E-G Construction.pdf
E.		Roof, sidewall, and flooring drawings showing structure and structural specifications indicating metal size and type used. Include side sheathing and inside panels.	Turtle Top-C-D-E-G Construction.pdf
F.		Manufacturer's chassis description (specifications).	Turtle Top-F-Chassis E3F DD 138 WB MDOT.pdf Turtle Top-F-Chassis E3F SD 158 WB MDOT.pdf Turtle Top-F-Chassis E4F SD 158 WB MDOT.pdf
G.		Detailed engineering drawings of the body to chassis frame mounting.	Turtle Top-C-D-E-G Construction.pdf
H.		Manufacturer's technical specifications for wheelchair lifts and wheelchair restraints. Manufacturer's sales literature is acceptable if it contains the technical specifications.	Turtle Top-H-Wheelchair Components.pdf
I.		The warranties for body, chassis, and drive train.	Turtle Top-I-Warranty.pdf
J.		If applicable, as required by Title 49 of the CFR, Part 663 – Subpart D, a copy of the manufacturer's self-certification information concerning the bus's compliance with relevant Federal Motor Vehicle Safety Standards (pre-award)	Turtle Top-J-FMVSS Certification 2025.pdf
K.		A copy of the Bus Rollover Protection Test (FMVSS 220), 49CFR §571.220 and School Bus Joint Strength (FMVSS 221), 49CFR § 571.221 results of the bus offered as specified in the bid.	Turtle Top-K-FMVSS 220 Test Complete.pdf
L.		Completed Schedule C - Federal Transit Administration (FTA) clauses shall be attached to bid quotation.	Turtle Top-A-Schedule E - Federally Required Contract Clauses Signed By TESCO.pdf Turtle Top-A-Schedule E - Federally Required Contract Clauses Signed By Turtle Top.pdf Turtle Top-L-FY25 DBE Turtle Top Bus.pdf Turtle Top-L-Turtle Top Bus FTA Compliance.pdf
M.		Buy America analysis of manufacturer's list of component and subcomponent parts (pre-award).	Turtle Top-M-Buy America Certifications.pdf
N.		The technical data sheet including flammability and smoke emissions for the seat covering material supplied.	Turtle Top-N-Seat Cover TDS.pdf

Transportation Equipment Sales Corporation – Turtle Top

O.		Seat frame salt spray test data and impact resistance test results.	Turtle Top-O-Seat Salt Spray Testing.pdf
P.		Certification test data showing that the seats, the seat belts, and the installation are in compliance with FMVSS-207, 208, 209, and 210 where applicable for the bus model being offered in this bid.	Turtle Top-P-Seat Testing.pdf
Q.		Technical data sheet for the seat cushion foam supplied.	Turtle Top-Q1-Reiss Industries Foam Specs.pdf
R.		Certification that the wiring and the switches for air conditioning and all add-on components are adequate to withstand transient loads expected.	Turtle Top-R-Statement of Bus and Component Wiring.pdf Turtle Top-R-TransAir System Approval Letter_Electric.pdf
S.		Proof of valid motor vehicle dealer licensing from state, county, or municipality.	Turtle Top-S-Dealers License Expires 2026.pdf
T.		A copy of the dealer agreement between the Bus Manufacturer and the designated bidder.	Turtle Top-T-TESCO Dealer Agreement Signed.pdf
U.		Certification that the bus model offered is a 5 year or 150,000 mile (small class one) or 7 years/200,000 mile (small class two) bus and will meet the requirements of Federal Register Rules and Regulations 49 CFR Part 665, Bus Testing Program. Stating from § 665.13 Test Report and Manufacturer Certification, Section (b)(1), "A manufacturer of a new bus model or a bus produced with a major change in component or configuration shall provide a copy of the test report to a recipient during the point in the procurement process specified by the recipient".	Turtle Top-Y-1 Terra Transit Altoona Report.pdf Turtle Top-Y-2 Ford E450 6.8 L Engine Altoona Report.pdf Turtle Top-Y-3 FTA Letter regarding Ford 7-3L engine.pdf
V.		Certification for 480-hour salt spray test per ASTM procedure B-117.	Turtle Top-V-W-X-Salt-Humidity.pdf
W.		Certification for 1,000-hour salt spray test per ASTM procedure B-117.	Turtle Top-V-W-X-Salt-Humidity.pdf
X.		480 hour ASTM D2247 Humidity Resistance test.	Turtle Top-V-W-X-Salt-Humidity.pdf
Y.		<u>FULL</u> Altoona Test Report.	Turtle Top-Y-1 Terra Transit Altoona Report.pdf Turtle Top-Y-2 Ford E450 6.8 L Engine Altoona Report.pdf Turtle Top-Y-3 FTA Letter regarding Ford 7-3L engine.pdf
Z.		Schedule D - Affidavit for Driver Delivery	Turtle Top-Z-Schedule D - Affidavit for Driver Delivery.pdf
AA.		Bus turning radius: wheel-to-wheel	Turtle Top-AA and BB Turning Radius Chart.pdf
BB.		Bus turning radius: wall-to-wall	Turtle Top-AA and BB Turning Radius Chart.pdf
IX	EXCEPTIONS - List all exceptions in the space below:		
Turtle Top will not allow resettable circuit breakers in the main electrical panel of the bus due to the potential of operators resetting a faulty circuit which could result in a fire. Class I, Floorplans A & B do not have a co-pilot seat.			

Transportation Equipment Sales Corporation – Turtle Top

X	BIDDER COMMENTS
Additional documentation submitted but not listed above starts with the prefix “ZZ”.	